



**Bergmann dumpers.**  
The models.

**Bergmann. Built for you.**



Made in Germany.

**BERGMANN**

# For safety. A Bergmann.

Premium quality made in Germany.  
High value stability. And maximum  
operational safety. With these  
features we will also be able to  
convince you. Take us at our word.  
**[www.bergmann-dumper.de](http://www.bergmann-dumper.de)**

# Ready for the future.

## New names. New opportunities. Worldwide.

All Bergmann vehicles have had new names since 2020.

With this strategic step, we are adapting our system to the international market and are thus setting the course for further expansion. For you, everything remains the same: Bergmann will continue to stand for first-class quality "Made in Germany".

Market segment:  
"Construction"

# C815s

"short tons"

Category: "Wheels + Driver"

Size:

"Payload carrier vehicle"



Bergmann 2060

**C 807 s**



Bergmann 3012

**C 815 s**



Bergmann 4010

**C 912 s**

# Compact dumpers

Fast and manoeuvrable.

## ➤ **Best overview**

A short tail and a high sitting position ensure the operator the best all-round overview.

For quick and safe work.

## ➤ **Year-round use**

Thanks to a collapsible weather protection roof (optional). In focus: health protection, profitability, transport costs.

## ➤ **Safety for the operator**

The operator enters the dumper outside the danger area. Because safety is the priority, right from the start.



**C805s | C807s | C810s**

compact dumper | open  
swivel tip



## **C 805 s**

**NEW**

### Swivel-tip dumper

<b>Payload</b>	<b>4,500 kg</b>	<b>9,921 lb</b>
<b>Capacity level</b>	<b>1.9 m<sup>3</sup></b>	<b>2.5 yd<sup>3</sup></b>
<b>Capacity heaped</b>	<b>2.6 m<sup>3</sup></b>	<b>3.4 yd<sup>3</sup></b>
Total length	4,256 mm	13.96 ft
Total width	1,800 mm	5.91 ft
Clearance height without beacon light	2,765 mm	9.07 ft
Ground clearance	305 mm	1.00 ft
Dumping height	979 mm	3.21 ft
Load height (front)	1,677 mm	5.50 ft
Engine power		53 kW
Empty weight	3,300 kg	7,275 lb



## **C 807 s**

### Swivel-tip dumper

<b>Payload</b>	<b>6,000 kg</b>	<b>13,228 lb</b>
<b>Capacity level</b>	<b>2.5 m<sup>3</sup></b>	<b>3.3 yd<sup>3</sup></b>
<b>Capacity heaped</b>	<b>3.6 m<sup>3</sup></b>	<b>4.7 yd<sup>3</sup></b>
Total length	4,575 mm	15.01 ft
Total width	2,043 mm	6.70 ft
Clearance height without beacon light	3,087 mm	10.13 ft
Ground clearance	326 mm	1.07 ft
Dumping height	1,141 mm	3.74 ft
Load height (front)	1,862 mm	6.11 ft
Engine power		55 kW
Empty weight	4,205 kg	9,270 lb



## **C 810 s**

### Swivel-tip dumper

<b>Payload</b>	<b>9,000 kg</b>	<b>19,842 lb</b>
<b>Capacity level</b>	<b>3.6 m<sup>3</sup></b>	<b>4.7 yd<sup>3</sup></b>
<b>Capacity heaped</b>	<b>4.6 m<sup>3</sup></b>	<b>6.0 yd<sup>3</sup></b>
Total length	5,050 mm	16.57 ft
Total width	2,420 mm	7.94 ft
Clearance height without beacon light	3,239 mm	10.63 ft
Ground clearance	313 mm	1.03 ft
Dumping height	1,175 mm	3.85 ft
Load height (front)	2,127 mm	6.98 ft
Engine power		75 kW
Empty weight	6,200 kg	13,669 lb

# Wheel dumpers

Masterful at any construction site.

## ➤ **Best all-terrain traction**

With large tyres, articulated swivel joint and spring suspension front axle, the C815s also safely handles rough terrain under its wheels.

## ➤ **A real performer**

In addition to high performance technology, the cab with its rotating driver's stand (optional) enables fast, safe work.

## ➤ **For any requirements**

Rear, three-way, swivel-tip or carrier vehicle with quick-change apparatus, your Bergmann has the equipment you need for your construction site.



**C815s | C828s**  
wheel dumper | cab  
rear, three-way or  
swivel tip



## **C 815 s**

### Rear tip dumper

<b>Payload</b>	<b>12,000 kg</b>	<b>26,455 lb</b>
<b>Capacity level</b>	<b>5.0 m<sup>3</sup></b>	<b>6.5 yd<sup>3</sup></b>
<b>Capacity heaped</b>	<b>8.0 m<sup>3</sup></b>	<b>10.5 yd<sup>3</sup></b>
Total length	6,834 mm	22.42 ft
Total width	2,505 mm	8.22 ft
Clearance height without beacon light	3,028 mm	9.93 ft
Ground clearance	429 mm	1.41 ft
Dumping height	923 mm	3.03 ft
Load height (front)	2,230 mm	7.32 ft
Engine power		119 kW
Empty weight	9,080 kg	20,017 lb



## **C 815 s**

### Three-way tip dumper

<b>Payload</b>	<b>12,000 kg</b>	<b>26,455 lb</b>
<b>Capacity level</b>	<b>4.2 m<sup>3</sup></b>	<b>5.5 yd<sup>3</sup></b>
<b>Capacity heaped</b>	<b>8.0 m<sup>3</sup></b>	<b>10.5 yd<sup>3</sup></b>
Total length	7,593 mm	24.42 ft
Total width	2,541 mm	8.34 ft
Clearance height without beacon light	3,028 mm	9.93 ft
Ground clearance	429 mm	1.41 ft
Dumping height	449 mm	1.47 ft
Load height (front)	2,052 mm	6.73 ft
Engine power		119 kW
Empty weight	10,020 kg	22,090 lb



## **C 815 s**

### Swivel-tip dumper

<b>Payload</b>	<b>12,000 kg</b>	<b>26,455 lb</b>
<b>Capacity level</b>	<b>6.3 m<sup>3</sup></b>	<b>8.5 yd<sup>3</sup></b>
<b>Capacity heaped</b>	<b>8.0 m<sup>3</sup></b>	<b>10.5 yd<sup>3</sup></b>
Total length	7,129 mm	23.39 ft
Total width	2,500 mm	8.20 ft
Clearance height without beacon light	3,028 mm	9.93 ft
Ground clearance	424 mm	1.40 ft
Dumping height	1,441 mm	4.73 ft
Load height (front)	2,442 mm	8.01 ft
Engine power		119 kW
Empty weight	11,140 kg	20,017 lb



## **C 828 s**

### Rear tip dumper

<b>Payload</b>	<b>25,000 kg</b>	<b>55,116 lb</b>
<b>Capacity heaped</b>	<b>15.0 m<sup>3</sup></b>	<b>19.6 yd<sup>3</sup></b>
Total length	9,316 mm	30.56 ft
Total width	2,870 mm	9.42 ft
Clearance height without beacon light	3,353 mm	11.00 ft
Ground clearance	480 mm	1.57 ft
Dumping height	700 mm	2.30 ft
Load height (front)	2,719 mm	8.92 ft
Engine power		194 kW
Empty weight	19,250 kg	42,439 lb

# Our underground specialists.

## ➤ **Maximum safety**

With its ergonomic reversible seat, the tunnel dumpers offer an excellent view of the work environment from every direction of travel.

## ➤ **High work efficiency**

With work speeds up to 40 km/h forwards and 30 km/h backwards, the C828s is the ideal transport vehicle for tunnelling and mining.

## ➤ **A cost-effective powerhouse**

High-performing yet cost-effective. The 2-axle design ensures low tyre and track wear and makes the articulated 6.7-litre diesel vehicle a cost-effective powerhouse.

**Built for the  
tunnel.**

# Track dumpers

Strong on any substrate.

## ➤ High speed

With a well-conceived safety concept and a driving speed of up to 15 km/h, C912s is convincing even on the most difficult substrate. Safe and high-performing.

## ➤ Economical and low-emission

State-of-the-art engine technology convinces with low diesel consumption and low emission values. Economical and environmentally friendly.

## ➤ Convincing ergonomics

The spacious driver's cab with rotating operator stand (optional) makes turning manoeuvres superfluous. Efficient and back-friendly.



**C912s**

track dumper | cab  
rear or swivel tip



# /// C 912 s

## Rear tip dumper

<b>Payload</b>	<b>10,000 kg</b>	<b>22,046 lb</b>
<b>Capacity level</b>	<b>4.7 m<sup>3</sup></b>	<b>6.1 yd<sup>3</sup></b>
<b>Capacity heaped</b>	<b>6.5 m<sup>3</sup></b>	<b>8.5 yd<sup>3</sup></b>
Total length	5,963 mm	19.56 ft
Total width	2,900 mm	9.51 ft
Clearance height without beacon light	3,050 mm	10.01 ft
Ground clearance	613 mm	2.01 ft
Dumping height	797 mm	2.61 ft
Load height (front)	1,998 mm	6.56 ft
Engine power		180 kW
Empty weight	14,250 kg	31,415 lb



# **C 912 s**

## Swivel-tip dumper

<b>Payload</b>	<b>10,000 kg</b>	<b>22,046 lb</b>
<b>Capacity level</b>	<b>4.7 m<sup>3</sup></b>	<b>6.1 yd<sup>3</sup></b>
<b>Capacity heaped</b>	<b>6.5 m<sup>3</sup></b>	<b>8.5 yd<sup>3</sup></b>
Total length	6,246 mm	20.49 ft
Total width	2,900 mm	9.51 ft
Clearance height without beacon light	3,050 mm	10.01 ft
Ground clearance	613 mm	2.01 ft
Dumping height	1,058 mm	3.47 ft
Load height (front)	2,207 mm	7.24 ft
Engine power		180 kW
Empty weight	14,850 kg	32,738 lb



## **C 912 s**

### Carrier vehicle

<b>Payload</b>	<b>11,200 kg</b>	<b>24,691 lb</b>
Total length	5,674 mm	18.62 ft
Total width	2,900 mm	9.51 ft
Clearance height without beacon light	3,050 mm	10.01 ft
Ground clearance	613 mm	2.01 ft
Engine power		180 kW
Empty weight	13,250 kg	29,211 lb

# Solutions



Completely individual in accordance with your requirements.

**Contact us!**

T +49 (0) 5932 7292-0

# What makes a Bergmann so safe:

1. High level of operational safety thanks to robust, durable, and certified technology
2. Rotating operator stand for maximum operational safety
3. Spring suspension rear axle for driving comfort and health protection
4. Safe entry and exit outside the danger area
5. Weather protection roof for a healthy work environment
6. Retractable bucket chute for working at a safe distance from the building pit
7. Permanent stability monitoring with warning function for quick and safe work
8. Investment security through partnership at eye level with an established family-owned company



**For safety.  
A Bergmann.**

All illustrations, dimensions and weights do not necessarily correspond to the standard equipment and are non-binding with regard to tolerance deviations on component level. We reserve the right to make technical changes.

**Bergmann. Built for you.**

**Bergmann Maschinenbau GmbH & Co. KG**

Essener Straße 7 | 49716 Meppen | T +49 (0) 5932 7292-0  
info@bergmann-mb.de | [www.bergmann-dumper.de](http://www.bergmann-dumper.de)