



Lifting Hose Units HE

For use with the JUMBOMOBIL JM, JUMBO-BV, TRANSMOBIL TM, MULTIMOBIL MM, JUMBO Travelling Crane JWK or on any other crane carrier.

(Application of lifting hose unit HE-250 is not to be operated with JUMBOMOBIL and MULTIMOBIL MM).

Consists of:

Transportation hook.

Rotational Device and quick coupling, 2 inch.

Lifting hose unit with protective fabric as well as a flange for fitting onto the operating valve unit.

Available optionally for HE-150/200/250: reinforced belt stay with buckle.

HE-35 – HE-250

| Type | Diameter mm (in) | Height Lifting Height mm (in) | Working Load Limit/WLL -420 mbar kg (lbs) | Order-Number |
|--------|------------------|-------------------------------|---|--------------|
| HE-35 | 120 (4¾) | 1,700 (67) | 35 (75) | 42100001 |
| HE-50 | 140 (5½) | 1,700 (67) | 50 (110) | 42100106 |
| HE-85 | 178 (7) | 1,700 (67) | 85 (185) | 42100002 |
| HE-150 | 230 (9) | 1,500 (59) | 150 (330) | 42100132 |
| HE-200 | 250 (9¾) | 1,500 (59) | 200 (440) | 42101114 |
| HE-250 | 300 (11¾) | 1,500 (59) | 250 (550) | 42101115 |



Operating Valve Unit BE-SPRINT-2

For direct coupling onto the lifting unit HE.

Longer operating handles on request.

Scope of delivery:

BE-SPRINT-2: Main body with handle 500 mm (19½ inch) long, fixing screw for adjusting the hovering position, safety gauge.

BE-SPRINT-2

| Type | Description | Dead Weight kg (lbs) | Order-Number |
|-------------|------------------------|----------------------|--------------|
| BE-SPRINT-2 | for HE-35 up to HE-250 | 8.5 (20) | 42100539 |